

KPT-39 Remote Keypad Series with Proximity Reader

Easy and Secure Access at Your Fingertips



- A 15-button backlit keypad
- Integrate RFID key fobs or NFC tags

KPT-39 is a smart wireless remote keypad, offering users an easy-to-program solution to easily arm, disarm, and home arm their security system. For enhanced flexibility and convenience, KPT-39 series can integrate with RFID key fobs or NFC tags for secure quick access without entering pin codes manually.

To provide additional peace of mind and safety, KPT-39 series features dual key function that can activate panic, fire, or medical emergency alarm at the touch of a button. KPT-39 keypad can be wall-mounted at any location that is the most convenient and the most accessible in users' homes. KPT-39 is safeguarded by tamper protection.

KPT-39 leverages Climax's industry-leading RF technology to accelerate the speed of signal transmission and deliver reliable, extensive communication range. KPT-39 also features a power conservation function that consumes power only when in operation.

Features

- Enables user to arm/disarm/home arm the security system by simply swiping RFID key fobs or NFC tags
- Integrates up to 100 RFID key fobs or NFC tags
- Dual key buttons to trigger panic, fire, or medical emergency alarms
- Stand-by mode for power saving function
- LED status indicators
- EN50131 Grade 2, Class II, and INCERT certified
- A 15-button backlit keypad for easy nighttime visibility
- Tamper protection against unauthorized removal
- Extensive RF communication range and faster signal transmission
- Entry/Exit sound
- Regular supervision signals to check system integrity
- IP44 waterproof standard

Specifications

KPT-39-F1

Frequency	868 MHz / 433 MHz
Power Source	3V, CR123 Lithium battery x 1
Battery Life	5.3 years*
Key Fob Reader Protocol	ISO 15693
Waterproof Rating	IP44
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	120 mm x 90 mm x 30 mm

KPT-39 Remote Keypad Series with Proximity Reader

KPT-39N-F1

Frequency	868 MHz / 433 MHz
Power Source	3V, CR123 Lithium battery x 1
Battery Life	5.3 years*
NFC Tag Dimensions	45 mm x 25 mm
NFC Protocol	ISO 14443A
Waterproof Rating	IP44
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	120 mm x 90 mm x 30 mm

**Note: Actual battery life may vary due to device settings, operating environment and usage activity.*

Ordering Information

KPT-39-F1	Remote Keypad and RFID Key Fob
KPT-39N-F1	Remote Keypad and NFC Tag