



Teclados con display gráfico y ayuda hablada

Los teclados SPCK620 y SPCK623 de Vanderbilt constituyen un medio de acceso completo e intuitivo al sistema SPC. Están optimizados para un fácil manejo de varias particiones. La versión SPCK623 dispone de lector de tarjetas y ayuda hablada al usuario.

Key Features

- Estructura mediante menús y submenús de fácil comprensión.
El display gráfico, el teclado y los cursores de navegación son muy eficaces en el manejo de sistemas dotados de varias particiones, haciendo que el control sea verdaderamente amigable, gracias además a la ayuda hablada.
- Lector integrado de tarjetas en el modelo SPCK623.
Manejo aún más fácil para armar, desarmar, abrir puertas, etc. sin necesidad de código o más seguro empleándolo junto con un código.
- Verificación de audio en el modelo SPCK623.
La inclusión de un interfono (altavoz y micrófono) permite emplearlo para verificar alarmas por audio, con tiempos de grabación pre/post alarma configurables, asignándolo a una zona de verificación. También es posible la función habla/escucha en vivo con el operador de la CRA.
- Fáciles configuración y uso.
Aunque SPC cuenta con fáciles y potentes herramientas de configuración mediante software y página web, esta tarea puede ser también llevada a cabo desde estos teclados. Para el usuario, las teclas soft para emergencia, armado rápido, etc. y los cursores de navegación proporcionan un uso fácil con un mínimo de pasos. El display puede representar un reloj analógico y el logotipo del cliente.

Keypad Operations

- Menús de programación
- Menús para usuarios
- Estado del sistema
- Ayuda hablada que facilita el manejo
- Acceso fácil a varias particiones
- Control de macros
- Gestión de usuarios
- Configuración de SMS
- Acceso a registro de eventos
- Idioma personalizado a cada usuario
- Control de puertas
- Etc.



Technical Data	
Funcionalidad	
Indicadores LED	5 LEDs de estado
4, programables	4 teclas software y cursores de navegación por los menús
Intrusion	
Interfaces	4 hilos para alimentación y X Bus (E/S)
Alimentación y medidas	
Dimensiones	185 (alto) x 112 (ancho) x 28 (espesor)
Corriente de funcionamiento	SPCK620 - Máximo 155 mA a 12 Vcc (iluminación, LEDs y ayuda hablada activados) SPCK623 - Máximo 230 mA a 12 Vcc (iluminación, LEDs y ayuda hablada activados)
Temperatura de operación	5° a +40 °C
Tensión de operación	9,5 a 14 Vcc
Corriente en reposo	SPCK620 - Máximo 55 mA a 12 Vcc SPCK623 - Máximo 110 mA a 12 Vcc
Tamper	Delantero y trasero, accionados por pulsador con muelle
General	
Color	RAL 9003 (blanco señal)
Display	128 x 64 pixels (aproximadamente 6 x 20 caracteres)
Peso	380 g



SPCK620.100-N Comfort KP, Neutr.

Teclados confort SPC

Ordering Data

Type	Art. No.	Description	Weight*
Keypad	V54543-F110-A100	SPCK620.100 Comfort Keypad	0.380 kg
Keypad	V54543-F111-A100	SPCK623.100 Comfort Keypad w. Reader / Audio	0.380 kg
SPCY620	V54543-Z150-A100	Flush mount Kit	

* Total weight of the product inclusive of the weight of its accessories and packaging.

Additional Ordering Data

Acre intrusion Panels

Type	Art. No.	Description
SPC6350.320-L1	V54541-C118-A100	Acre intrusion control panel, 16-512 zones, Ethernet, G5 metal housing
SPC6330.320-L1	V54541-C105-C100	Acre intrusion control panel, 8-512 zones, Ethernet, G3 metal housing
SPC5350.320-L1	V54541-C117-A100	Acre intrusion control panel, 16-128 zones, Ethernet, G5 metal housing
SPC5330.320-L1	V54541-C107-B100	Acre intrusion control panel, 8-128 zones, Ethernet, G3 metal housing
SPC5320.320-L1	V54541-C106-B100	Acre intrusion control panel, 8-128 zones, Ethernet, G2 metal housing
SPC4320.320-L1	V54541-C109-B100	Acre intrusion control panel, 8-32 zones, Ethernet, G2 metal housing
SPC4320.220-L1	V54541-C114-A100	Acre intrusion control panel, 8-32 zones, Ethernet, G2 housing with metal base and plastic cover

Keypads

Type	Art. No.	Description
SPCK520.100-N	V54543-F115-A100	Compact Keypad with graphical display and audio
SPCK521.100-N	V54543-F116-A100	Compact Keypad with graphical display, card reader and audio
SPCK620.100	V54543-F110-A100	LCD keypad with graphical display
SPCK623.100	V54543-F111-A100	LCD keypad with graphical display, card reader and audio
SPCK420.100	V54543-F101-A100	LCD keypad with 2 x 16 characters
SPCK421.100	V54543-F102-A100	LCD keypad with 2 x 16 characters and integrated card reader

Detectors

Type	Art. No.	Description
PDM-I12	V54530-F114-A100	MAGIC PIR detector, 12m wide angle
PDM-I18	V54530-F106-A100	MAGIC PIR detector, 18 m wide angle
MK-1400	V54536-F101-A100	Magnetic contact

Accessories

Type	Art. No.	Description
IPAW8-10	V54538-F107-A100	Wireless personal alarm
IRCW6-11	V54543-F109-A100	SiWay remote control, white replaceable battery

IPAW6-10	V54538-F108-A100	Wireless Personal Alarm Button
----------	------------------	--------------------------------

Expanders

Type	Art. No.	Description
SPCE452.100	V54542-F107-A100	Expander with 8 outputs, back tamper
SPCE652.100	V54542-F106-A100	Expander with 8 inputs and 2 outputs, back tamper
SPCA210.100	V54547-A101-A100	2-door expander
SPCP432.300	V54545-C103-A100	Smart PSU with 2-door expander, G2-housing
SPCP433.300	V54545-C104-A100	Smart PSU with 2-door expander, G3-housing
SPCE110.100	V54542-F104-A100	Keyswitch expander with 2 LEDs and 3-position key switch
SPCE120.100	V54542-F105-A100	Indication expander with 16 LEDs, 4 function keys and integrated card reader
SPCW130.100	V54554-F101-B100	SiWay RF-expander
SPCP332.300	V54545-C102-A100	Smart PSU with 8 inputs and 2 outputs, G2-housing
SPCP333.300	S54545-C101-A100	Smart PSU with 8 inputs and 2 outputs, G3-housing
SPCP355.300	S54545-C105-A100	Smart PSU with 8 inputs and 6 outputs, G5 metal housing

Verification

Type	Art. No.	Description
SPCV340.000	V54542-F108-B100	Audio expander with 4 inputs and 1 output
SPCV341.000	V54542-F109-B100	Audio expander with 4 inputs and 1 line output
SPCV310.000	V54542-F120-A100	Audio satellite
SPCV440.000	V54542-F118-A100	Combi audio expander for MAGIC motion detectors with 4 inputs and 1 output
SPCV410.000	V54542-F119-A100	Combi audio satellite for MAGIC motion detectors
CCMS2010-IR	S54561-C112-A100	1/2.7" 2MP Compact IP Camera PoE(LAN)

Access

Type	Art. No.	Description
AR6181-MX	6FL7170-8BK	Multi-technology card reader
PP500-EM	V54501-F1-A1	Heavy-duty card and PIN reader
AR6182-RX	6FL7170-8AE	Multi-technology card and PIN reader